

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

FILING RECEIPT



UNITED STATES DEPARTMENT OF COMMERCE
Patent and Trademark Office
ASSISTANT SECRETARY AND COMMISSIONER
OF PATENTS AND TRADEMARKS
Washington, D.C. 20231

APPLICATION NUMBER	FILING DATE	GRP ART UNIT	FIL FEE REC'D	ATTORNEY DOCKET NO.	DRWGS	TOT CL	IND CL
09/381,508	09/21/99	3629	\$1,074.00	1749-258	2	15	6

000826
ALSTON & BIRD LLP
P O DRAWER 34009
CHARLOTTE NC 28234-4009

Alston & Bird

JAN 18 2000

Received By [Signature]

Receipt is acknowledged of this nonprovisional Patent Application. It will be considered in its order and you will be notified as to the results of the examination. Be sure to provide the U.S. APPLICATION NUMBER, FILING DATE, NAME OF APPLICANT, and TITLE OF INVENTION when inquiring about this application. Fees transmitted by check or draft are subject to collection. Please verify the accuracy of the data presented on this receipt. If an error is noted on this Filing Receipt, please write to the Office of Initial Patent Examination's Customer Service Center. Please provide a copy of this Filing Receipt with the changes noted thereon. If you received a "Notice to File Missing Parts of Application" ("Missing Parts Notice") in this application, please submit any corrections to this Filing Receipt with your reply to the "Missing Parts Notice." When the PTO processes the reply to the "Missing Parts Notice," the PTO will generate another Filing Receipt incorporating the requested corrections (if appropriate).

Applicant(s) PAUL DAVID METCALFE, PETERCULTER, UNITED KINGDOM.

CONTINUING DATA AS CLAIMED BY APPLICANT-

THIS APPLN IS A 371 OF PCT/GB98/00863 03/20/98


FOREIGN APPLICATIONS-	UNITED KINGDOM	9705928.1	03/21/97
	UNITED KINGDOM	9723338.1	11/04/97

IF REQUIRED, FOREIGN FILING LICENSE GRANTED 01/12/00

TITLE

EXPANDABLE SLOTTED TUBING STRING AND METHOD FOR CONNECTING
SUCH A TUBING STRING

PRELIMINARY CLASS: 285



DATA ENTRY BY: ORDONEZ, MARTA

TEAM: 11 DATE: 01/12/00

(See reverse for new important information)

LICENSE FOR FOREIGN FILING UNDER
Title 35, United States Code, Section 184
Title 37, Code of Federal Regulations, 5.11 & 5.15

GRANTED

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "FOREIGN FILING LICENSE GRANTED" followed by a date appears on the reverse side of this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.11. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.

This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related application(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the national security or the export of technical data. Licensees should apprise themselves of current regulations, especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR Parts 121-128)); the Office of Export Administration, Department of Commerce (15 CFR 370.10 (j)); the Office of Foreign Assets Control, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

NOT GRANTED

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "FOREIGN FILING LICENSE GRANTED" DOES NOT appear on the reverse side of this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).

PLEASE NOTE ---- The Following Information about the Filing Receipt:

The articles such as "a," "an" and "the" are not included as the first words in the title of an application. They are considered to be unnecessary to the understanding of the title.

The words "new," "improved," "improvement," "improvements in or relating to" are not included as the first words in the title of an application because a patent application is, by nature, a new idea or improvement.

The title may be truncated if it consists of more than 4 lines of 70 characters each (letters and spaces combined).

The inventor information may be truncated if the family name consists of more than 25 characters (letters and spaces combined) and if the given name consists of more than 25 characters (letters and spaces combined). The inventor's residence allows for up to 40 characters (letters and spaces combined).

The docket number allows a maximum of 12 characters.

If your application was submitted under 37 CFR 1.10, your filing date should be the "date in" found on the Express Mail label. If there is a discrepancy, you should submit a request for a corrected Filing Receipt along with a copy of the Express Mail label showing the "date in."

Customer Address may have been modified to conform to U.S. Postal rules.

Please direct correction, including a copy of your Filing Receipt, to:
Assistant Commissioner for Patents
Office of Initial Patent Examination
Customer Service Center
Washington, DC 20231

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: E21B 17/08, 43/10, 43/08, F16L 13/14		A1	(11) International Publication Number WO 98/42947
(21) International Application Number: PCT/GB98/00863		(43) International Publication Date 1 October 1998 (01.10.98)	
(22) International Filing Date: 20 March 1998 (20.03.98)		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(30) Priority Data: 9705928.1 21 March 1997 (21.03.97) GB 9723338.1 4 November 1997 (04.11.97) GB		Published With international search report. Before the expiration of the time limits for amending the claims and to be republished in the event of the receipt of amendments.	
(71) Applicant (for all designated States except US): PETROLINE WELLSYSTEMS LIMITED (GB/GB); Offshore Technology Park, Claymore Drive, Bridge of Don, Aberdeen AB23 8GD (GB).			
(72) Inventor, and (75) Inventor/Applicant (for US only): METCALFE, Paul, David (GB/GB); North Wing, Buckleburn Seading, Peterculter AB14 0NP (GB).			
(74) Agents: McCALLUM, William, Potter et al.; Croilshank & Fairweather, 19 Royal Exchange Square, Glasgow G1 3AE (GB).			

(54) Title: EXPANDABLE SLOTTED TUBING STRING AND METHOD FOR CONNECTING SUCH A TUBING STRING



(57) Abstract

An expandable tubing assembly comprises a tubular connector (16) defining overlapping longitudinal slots (18), the connector (16) comprising end portions (20, 21) and an intermediate portion (22). The slots (18) extend over the whole length of the connector (16), but the only slot overlap occurs in the intermediate portion (22). The assembly further comprises lengths of expandable tubing (24, 25) defining overlapping longitudinal slots (12) and having end portions defining nodes (38) between and beyond the ends of the tubing slots (12). Tubing threads (28, 29) are formed on the end most tubing nodes. The connector and portions define threads (26, 27) and are coupled with the threads (28, 29) formed on the nodes of the respective end portions of the tubing lengths.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SV	Sweden
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TC	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Cote d'Ivoire	KR	Republic of Korea	PL	Poland		
CM	Cameroon	KZ	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

1749-258

U.S. APPLICATION NO. (If known, see 37 C.F.R. 1.5)

INTERNATIONAL APPLICATION NO.

INTERNATIONAL FILING DATE

PRIORITY DATE CLAIMED

PCT/GB98/00863

MARCH 20, 1998

MARCH 21, 1997

TITLE OF INVENTION

"EXPANDABLE SLOTTED TUBING STRING AND METHOD FOR CONNECTING SUCH A TUBING STRING"

APPLICANT(S) FOR DO/EO/US

Paul David Metcalfe

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(I).
4. ☐ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☒ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☐ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☒ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. To 16. Below concern other document(s) or information included:

11. ☐ An Information Disclosure Statement under 37 C.F.R. 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A **FIRST** preliminary amendment.
☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☐ Other items or information:

U.S. APPLICATION NO. (If known, see 37 C.F.R. 1.50)	INTERNATIONAL APPLICATION NO. PCT/GB98/00863	ATTORNEY'S DOCKET NUMBER 1749-258
---	---	--------------------------------------

17. <input checked="" type="checkbox"/> The following fees are submitted: Basic National Fee (37 CFR 1.492(a)(1)-(5)): Neither international preliminary examination fee (37 CFR 1.482) nor International search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO. \$970.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO. \$840.00 International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search (37 CFR 1.445(a)(2)) paid to USPTO. \$760.00 International preliminary examination fee (37 CFR 1.482) paid to USPTO. \$670.00 But all claims did not satisfy provisions of PCT Article 33(1)-(4). \$ 96.00 International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4). \$ 96.00 ENTER APPROPRIATE BASIC FEE AMOUNT =	<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th style="width:50%;">CALCULATIONS</th> <th style="width:50%;">PTO USE ONLY</th> </tr> <tr> <td colspan="2" style="height: 100px;"></td> </tr> </table>	CALCULATIONS	PTO USE ONLY		
CALCULATIONS	PTO USE ONLY				

Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).		\$
---	--	----

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total Claims	15 - 20 =	0	X \$18.00	\$ 0.00	
Independent Claims	6 - 3 =	3	X \$78.00	\$ 234.00	
MULTIPLE DEPENDENT CLAIM(S) (if applicable)				+ \$260.00	\$ 0.00
TOTAL OF ABOVE CALCULATIONS				=	\$ 1074.00

Reduction by 1/2 for filing by small entity, if applicable. A Small Entity statement must also be filed. (Note 37 CFR 1.9, 1.27, 1.28).		\$ 0.00
SUBTOTAL		= \$ 1074.00

Processing fee of \$130.00 for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).		\$ 0.00
TOTAL NATIONAL FEE		= \$ 1074.00

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property +		\$ 0.00
TOTAL FEES ENCLOSED		= \$ 1074.00



	Amount to be Refunded \$ Charged \$
--	--

a. ☒ A check in the amount of \$ 1074.00 to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account No. 16-0605 in the amount of \$ to cover the above fees. A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 16-0605. A duplicate copy of this sheet is enclosed.

Note: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137 (a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO: Samuel G. Layton, Jr.  SIGNATURE REGISTRATION NUMBER 22,807 ALSTON & BIRD LLP Post Office Drawer 34009 Charlotte, NC 28234 Tel. Charlotte Office (704) 331-6000 Fax Charlotte Office (704) 334-2014	"Express Mail" Mailing Label Number EL287630192US Date of Deposit: September 21, 1999 I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to BOX PCT, Attn: DO/US (PTO) Assistant Commissioner for Patents, Washington, DC 20231.  DENISE REAVES
---	--

EL287630192US

WO 92/42947

PCT/GB98/00863

5

slots overlap, the method comprising the steps of:

providing a sleeve defining overlapping longitudinal slots and deformable fingers of material where adjacent circumferentially spaced slots overlap;

5 coupling the sleeve to the ends of first and second lengths of expandable tubing such that the fingers of the sleeve are longitudinally spaced from the endmost fingers of the tubing lengths; and

10 forcing an expansion member through the connected tubing lengths to expand the sleeve and tubing lengths.

As used herein, the term slots is intended to encompass slots which extend through the walls of the sleeve and tubing, slots which extend only part way through the walls and any other appropriate weakening of the walls
15 such as lines of bores or scallops.

Preferably, the connecting means are provided at circumferentially spaced locations at the end of the tubing lengths beyond the endmost tubing fingers, and at the ends of the sleeve beyond the respective endmost tubing fingers.
20 The connecting means may comprise pins, rivets, screws and the like for location in appropriate aligned bores provided in the sleeve and tubing lengths. Single fasteners may be provided beyond each tubing finger, or multiple fasteners may be provided.

25 Preferably also, the unexpanded sleeve is of larger diameter than the tubing lengths. Most preferably, the sleeve and the tubing length are each of substantially constant diameter along their length.

WO 98/42947

PCT/GB98/00863

6

According to a still further aspect of the present invention there is provided an arrangement for coupling lengths of expandable tubing, the arrangement comprising a longitudinally slotted sleeve, first and second tubing lengths defining overlapping longitudinal slots, in use the tubing lengths being radially expandable by deformation of fingers of material where adjacent circumferentially spaced slots overlap, and connecting means for connecting the sleeve to the ends of the tubing lengths.

The sleeve may be in the form of longitudinally extending strips of metal. Most preferably, the strips are rectilinear. On expansion, the strips of the sleeve move radially outwardly and separate circumferentially. Initially, that is prior to expansion, the strips may be circumferentially connected, by frangible links such as wire, webs of material or one or more welds, to facilitate sleeve handling.

The invention further relates to a method for coupling the ends of first and second lengths of expandable tubing defining overlapping longitudinal slots and deformable fingers of material where adjacent circumferentially spaced slots overlap, the method comprising the steps of:

providing a sleeve comprising longitudinally extending strips of material;

coupling the sleeve to the ends of first and second lengths of expandable tubing; and

forcing an expansion member through the connected tubing lengths to expand the sleeve and tubing lengths.

WO 98/42947

PCT/GB98/00863

7

Preferably, the connecting means are provided at circumferentially spaced locations at the end of the tubing lengths beyond the endmost tubing fingers, and at the ends of the sleeve. The connecting means may comprise pins, rivets, screws and the like for location in appropriate aligned bores provided in the sleeve and tubing lengths. Single fasteners may be provided beyond each tubing finger, or multiple fasteners may be provided.

Preferably also, the unexpanded sleeve is of larger diameter than the tubing lengths. Most preferably, the sleeve and the tubing length are each of substantially constant diameter along their length.

These and other aspects of the present invention will now be described, by way of example, with reference to the accompanying drawings, in which:

Figure 1 is a sectional view of a length of expandable tubing, shown in an expanded configuration;

Figure 2 is a sectional view of an expandable tubing assembly in accordance with a first embodiment of the present invention;

Figure 3 is a schematic plan view of an arrangement for coupling lengths of expandable tubing in accordance with a second embodiment of the present invention;

Figure 4 is a sectional view of Figure 3; and

Figure 5 is a schematic plan view of an arrangement for coupling lengths of expandable tubing in accordance with a third embodiment of the present invention;

Reference is first made to Figure 1 of the drawings,

WO 98/42947

PCT/GB98/00863

8

which illustrates a length of expandable tubing 10. In its initial configuration, the tubing 10 is simply a length of pipe in which a series of longitudinal slots 12 have been machined. Applying a radially outward force to the tubing wall, by passing a mandrel through the tubing, causes the tubing to expand such that the slots 12 become diamond-shaped openings.

The tubing 10 is supplied in lengths suitable for transportation and handling and these are joined to one another on surface to create a tubular string. The assembly 14 illustrated in Figure 2 of the drawings allows lengths of expandable tubing 10 to be connected to form a string, as will now be described.

The assembly 14 comprises a tubular connector 16 defining overlapping longitudinal slots 18, the connector 16 comprising end portions 20, 21 and an intermediate portion 22. The slots 18 extend over the whole length of the connector 16, but the only slot overlap occurs in the intermediate portion 22.

The connector 16 is utilised to join the ends of two lengths of expandable tubing 24, 25, the ends of which are adapted to engage with the connector end portions 20, 21 as described below.

The connector intermediate portion 22 is of substantially the same wall thickness as the tubing 24, 25, however the connector end portions 20, 21 are upset, that is they include portions of greater wall thickness than the tubing 24, 25 and are of a greater diameter than the tubing

WO 98/42947

PCT/GB98/00863

9

24, 25. The inner walls of each connector end portion 20, 21 define threads 26, 27 for engaging corresponding threads 28, 29 on the outer surface of the tubing 24, 25. Inwardly of the threads 26, 27 the end portions 20, 21 define grooves 30, 31 to receive corresponding tongues 32, 33 provided on the ends of the tubing lengths 24, 25.

As noted above, the connector slots 18 only overlap in the intermediate portion 22, such that on expansion of the connector 16 and the tubing lengths 24, 25 the connector 16 is only subject to significant deformation in the intermediate portion 22, at and adjacent the slot overlap 34. The amount of deformation is substantially lower in the rest of the connector 16, particularly in the "nodes" 36 between the ends of the longitudinally aligned slots 18. The tubing lengths 24, 25 feature nodes 38 between and beyond the ends of the tubing slots 12 and the tubing threads 28, 29 are formed on the end most tubing nodes.

In use, the tubing lengths 24, 25 are connected by first making up the connector 16 to one tubing length 24, and then making up the second tubing length 25 to the other end of the connector 16. A number of tubing lengths are connected in this way to form a tubing string, which is run into a wellbore. Once in a desired position, an expansion mandrel is run through the tubing string, and radially extends the connector 16 and the tubing lengths 24, 25. In doing so, the connector slots 18 and tubing slots 12 are expanded to define diamond shaped openings, as are illustrated in Figure 1. As described above the connector

WO 98/42947

PCT/GB98/00863

10

is only subject to substantial deformation at the slot overlaps 34, such that the metal of the slot end portions 20, 21 is subject to minimal deformation. As the deformation of the metal of the connector occurs primarily in the intermediate portion 22, which is of corresponding diameter and thickness to the tubing 24, 25, the expansion properties of the connector 16 are similar to the tubing 24, 25, such that the connector 16 and tubing lengths 24, 25 will expand in corresponding and predictable manner, minimising the occurrence of irregularities in the internal diameter of the expanded tubing string.

From the above description it will be apparent to those of skill in the art that the assembly 14 provides a convenient means for connecting expandable tubing lengths. It is recognised that, for some applications, users may prefer to include coupling means between the connector end portions and the tubing lengths in addition to the thread connection, and in such cases screws, rivets, pins or the like may be provided to extend between the end portions 20, 21 and the tubing lengths 26, 27.

Reference is now made to Figures 3 and 4 of the drawings which will illustrate an arrangement 50 for connecting first and second lengths 52, 54 of expandable tubing utilising an expandable sleeve 56 secured to the ends of the tubing lengths 52, 54 by screws 58. The tubing walls 60, 61 and the sleeve wall 62 define overlapping longitudinal slots 64, 65, 66. Expansion of the tubing lengths 52, 54 and the sleeve 56 is accommodated by

WO 98/42947

PCT/GB98/00863

11

deformation of fingers of material 68, 69, 70 where the slots 64, 65, 66 overlap, and following deformation the slots 64, 65, 66 define diamond-shaped apertures. During expansion there is little or no deformation of the nodes 5 72, 73, 74 between the longitudinally spaced slots 64, 65, 66, and the screws 58 pass through bores in the endmost nodes 72, 73, 74 of the tubing lengths 52, 54 and the sleeve 56, at the ends of the tubing lengths 52, 54 and sleeve 56. Thus, the endmost deformable fingers of the 10 tubing lengths 68, 69 are axially spaced from the endmost fingers of the sleeve 70.

In use, the tubing lengths 52, 54 and sleeves 56 are shipped in disassembled form. The tubing lengths 52, 54 are made up on surface as the tubing is fed into the bore 15 in which the tubing is to be utilised. In particular, the ends of the tubing lengths 52, 54 are located in the respective ends of the sleeve 56. The screws 58 are then located and tightened in the screw bores. A number of tubing lengths are made up to provide the desired length of 20 tubing and the assembled tubing run into the bore. On reaching the desired location downhole, the tubing is anchored in place, and an expansion cone then pushed or pulled through the tubing. The cone expands the tubing length 52, 54 radially outwards such that, as mentioned 25 above, the slots 64, 65, 66 become diamond-shaped, with the expansion being accommodated by deformation of the fingers 68, 69, 70. The sleeve 56 deforms in a similar manner to the tubing lengths 52, 54. On moving through the

WO 98/42947

PCT/GB98/00863

12

arrangement 50, the expansion cone deforms, in turn, the endmost fingers 68 of the first tubing length 52, the fingers 70a at the first end of the sleeve 56, the fingers 70b at the second end of the sleeve 56, and finally the endmost fingers 69 of the second tubing length 54.

In testing it has been found that the forces required to expand the connecting arrangement 50 are the same or only slightly higher than the forces required to expand the tubing lengths 52, 54. Also, the expanded sleeve 56 tends to retain its expanded form, and suffers little or no diametrical shrinkage after the expansion cone has passed through the sleeve 56. Thus, the present invention avoids the difficulties experienced with previously proposed sleeve connectors. Further, the connection arrangement 50 is less expensive to produce than the male/female connectors as described in WO96/37687 and WO97/21901.

Reference is now made to Figure 5 of the drawings, which illustrates an alternative arrangement 110 for connecting first and second lengths 112, 114 of expandable tubing utilising an expandable sleeve 116 secured to the ends of the tubing lengths 112, 114 by screws 118. The tubing walls define overlapping longitudinal slots 124, 125. However, unlike the first described embodiment, the sleeve wall is formed of individual longitudinally extending strips 126. Expansion of the tubing lengths 112, 114 and the sleeve 116 is accommodated by deformation of fingers of material 128, 129 where the slots 124, 125 overlap, and circumferential separation of the sleeve

WO 98/42947

PCT/GB98/00863

13

strips 126. Following deformation the slots 124, 125
define diamond-shaped apertures. During expansion there is
little or no deformation of the nodes 132, 133 between the
longitudinally spaced slots 124, 125, and the screws 118
5 pass through bores in the endmost nodes 132, 133 of the
tubing lengths 112, 114 and the ends of the sleeve strips
126.

10 It will further be apparent to those of skill in the
art that the above-described embodiment is merely exemplary
of the present invention, and that various modifications
and improvements may be made thereto, without departing
from the scope of the present invention.

WO 98/42947

PCT/GB98/00863

14

CLAIMS

1. An expandable tubing assembly comprising:
a tubular connector defining overlapping longitudinal
slots and comprising slotted end portions; and
5 lengths of expandable tubing defining overlapping
longitudinal slots and having slotted end portions defining
nodes beyond the ends of the slots, the connector end
portions being coupled to the nodes of respective end
portions of the tubing lengths.
- 10 2. The assembly of claim 1, wherein the connector end
portions and the nodes of the tubing end portions are
threaded.
3. The assembly of claim 1 or 2, wherein the tubular
connector further comprises an intermediate portion between
15 the end portions.
4. The assembly of claim 3, wherein the slots extend over
the whole length of the connector, slot overlap occurring
only in the intermediate portion.
5. The assembly of claim 3 or 4 wherein the intermediate
20 portion is of corresponding configuration of the tubing
lengths, such that the expansion characteristics of the
connected tubing assembly are substantially constant over

WO 98/42947

PCT/GB98/00863

15

the connection.

6. The assembly of claim 5, wherein the connector intermediate portion is of substantially the same wall thickness of the tubing and wherein the connector end portions are upset.

7. The assembly of claim 6 wherein each connector end portion defines an internal thread for engaging a corresponding thread on an outer surface of the respective tubing end portion.

8. The assembly of any of the preceding claims wherein the connector end portions define grooves to receive corresponding tongues provided on the tubing length end portions.

9. A method of connecting lengths of expandable tubing defining overlapping longitudinal slots, the method comprising:

providing a tubular connector defining overlapping longitudinal slots and comprising end portions;

providing lengths of expandable tubing defining overlapping longitudinal slots and having end portions defining nodes beyond the ends of the slots; and

connecting the connector end portions to the nodes of respective end portions of the tubing lengths.

WO 98/42947

PCT/GB98/00863

16

10. An expandable tubing assembly comprising:

a tubular connector defining overlapping longitudinal slots, the connector comprising end portions and an intermediate portion; and

5 lengths of expandable tubing defining overlapping longitudinal slots and having end portions coupled to the connector end portions, at least the connector intermediate portion being of corresponding configuration to the tubing lengths, such that the expansion characteristics of the
10 intermediate portion and the tubing lengths correspond.

11. An arrangement for coupling lengths of expandable tubing, the arrangement comprising a sleeve defining overlapping longitudinal slots, first and second tubing lengths defining overlapping longitudinal slots, in use the
15 sleeve and tubing lengths being radially expandable by deformation of fingers of material where adjacent circumferentially spaced slots overlap, and connecting means for connecting the sleeve to the ends of the tubing lengths, the deformable fingers of the sleeve being axially
20 spaced from the end most deformable fingers of the respective tubing lengths.

12. The arrangement of claim 11, wherein the connecting means are provided at circumferentially spaced locations at the end of the tubing lengths beyond the end most tubing
25 fingers, and at the ends of the sleeves beyond the respective end most tubing fingers.

WO 98/42947

PCT/GB98/00863

17

13. The arrangement of claim 11 or 12, wherein the unexpanded sleeve is of larger diameter than the tubing lengths.

5 14. The arrangement of claim 13, wherein the sleeve and the tubing lengths are each of substantially constant diameter along their length.

15. A method for coupling the ends of first and second lengths of expandable tubing defining overlapping longitudinal slots and deformable fingers of material where
10 adjacent circumferentially spaced slots overlap, the method comprising the steps of:

providing a sleeve defining overlapping longitudinal slots and deformable fingers of material where adjacent circumferentially spaced slots overlap;

15 coupling the sleeve to the ends of first and second lengths of expandable tubing such that the fingers of the sleeve are longitudinally spaced from the end most fingers of the tubing lengths; and

20 forcing an expansion member through the connected tubing lengths to expand the sleeve and the tubing lengths.

16. An arrangement for coupling lengths of expandable tubing, the arrangement comprising a longitudinally slotted sleeve, first and second tubing lengths defining overlapping longitudinal slots, in use the tubing lengths
25 being radially expandable by deformation of fingers of

WO 98/42947

PCT/GD98/00863

18

material where adjacent circumferentially spaced slots overlap, and connecting means for connecting the sleeve to the ends of the tubing lengths.

5 17. The arrangement of claim 16, wherein the sleeve is formed of longitudinally extending strips of metal.

18. The arrangement of claim 17, wherein the strips are rectilinear.

10 19. The arrangement of claim 17 or 18, wherein the strips are initially circumferentially connected by frangible links.

15 20. A method for coupling the ends of first and second lengths of expandable tubing defining overlapping longitudinal slots and deformable fingers of material where adjacent circumferentially spaced slots overlap, the method comprising the steps of:

providing a sleeve comprising longitudinally extending strips of material;

coupling the sleeve to the ends of first and second lengths of expandable tubing; and

20 forcing an expansion member through the connected tubing lengths to expand the sleeve and tubing lengths.

INTERNATIONAL SEARCH REPORT

A. CLASSIFICATION OF SUBJECT MATTER IPC 6 E21B17/08 E21B43/10 E21B43/08 F16L13/14		Inventor and Application No PCT/GB 98/00863
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 6 E21B F16L		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used)		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X A X A A	WO 96 37681 A (PETROLINE WIRELINE SERVICES LIMITED) 28 November 1996 see page 5, line 21 - page 7, line 2 WO 96 37680 A (SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ) 28 November 1996 see page 5, line 1 - page 6, line 22; figures 3,4 WO 93 25800 A (SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ) 23 December 1993 cited in the application -/-	1-3,5-7, 9,10 11,15, 16,20 1-3,5-7, 9,10 11,15, 16,20
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C.		
<input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents : "A" documents defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claims or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "Z" document member of the same patent family		
Date of the actual completion of the international search 17 July 1998		Date of filing of the international search report 24/07/1998
Name and mailing address of the ISA European Patent Office, P.O. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040. Tx 31 651 epo nl Fax (+31-70) 340-3016		Authorized officer Sogno, M

INTERNATIONAL SEARCH REPORT

Information on parent family members

International Application No
PCT/G8 98/00863

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9637681 A	28-11-1996	AU 5826596 A	11-12-1996
		AU 7349396 A	11-12-1996
		WO 9637680 A	28-11-1996
		EP 0828918 A	18-03-1998
		EP 0824628 A	25-02-1998
		NO 975348 A	23-01-1998
		NO 975350 A	16-01-1998
WO 9637680 A	28-11-1996	AU 5826596 A	11-12-1996
		AU 7349396 A	11-12-1996
		EP 0828918 A	18-03-1998
		EP 0824628 A	25-02-1998
		WO 9637681 A	28-11-1996
		NO 975348 A	23-01-1998
		NO 975350 A	16-01-1998
WO 9325800 A	23-12-1993	AU 672008 B	19-09-1996
		AU 4324593 A	04-01-1994
		CA 2137565 A	23-12-1993
		DE 69305852 D	12-12-1996
		DE 69305852 T	22-05-1997
		DK 643795 T	14-04-1997
		EP 0643795 A	22-03-1995
		JP 7507611 T	24-08-1995
		MD 960219 A	31-05-1997
		NO 944746 A	03-02-1995
		NZ 253125 A	27-02-1996
		US 5366012 A	22-11-1994
WO 9721901 A	19-06-1997	AU 1068897 A	03-07-1997
WO 9822690 A	28-05-1998	NONE	

PATENT COOPERATION TREATY

-D AS

From the
INTERNATIONAL PRELIMINARY EXAMINING AUTHORITY

To:

McCALLUM, W.
CRUIKSHANK & FAIRWEATHER
19 Royal Exchange Square
Glasgow G1 3AE
GRANDE BRETAGNE

PCT

NOTIFICATION OF TRANSMITTAL OF
THE INTERNATIONAL PRELIMINARY
EXAMINATION REPORT
(PCT Rule 71.1)Date of mailing
(day/month/year)

19. 07. 99

Applicant's or agent's file reference
AS/HS/PO8180PC

IMPORTANT NOTIFICATION

International application No.
PCT/GB98/00863International filing date (day/month/year)
20/03/1998Priority date (day/month/year)
21/03/1997

Applicant

PETROLINE WELLSYSTEMS LIMITED et al.

1. The applicant is hereby notified that this International Preliminary Examining Authority transmits herewith the international preliminary examination report and its annexes, if any, established on the international application.
2. A copy of the report and its annexes, if any, is being transmitted to the International Bureau for communication to all the elected Offices.
3. Where required by any of the elected Offices, the International Bureau will prepare an English translation of the report (but not of any annexes) and will transmit such translation to those Offices.

4. REMINDER

The applicant must enter the national phase before each elected Office by performing certain acts (filing translations and paying national fees) within 30 months from the priority date (or later in some Offices) (Article 39(1)) (see also the reminder sent by the International Bureau with Form PCT/IB/301).

Where a translation of the international application must be furnished to an elected Office, that translation must contain a translation of any annexes to the international preliminary examination report. It is the applicant's responsibility to prepare and furnish such translation directly to each elected Office concerned.

For further details on the applicable time limits and requirements of the elected Offices, see Volume II of the PCT Applicant's Guide.

Name and mailing address of the IPEA/



European Patent Office
D-80298 Munich
Tel. (+49-89) 2399-0 Tx: 523655 apmu d
Fax: (+49-89) 2399-4465

Authorized officer

Riebel, O

Tel. (+49-89) 2399-2267





PATENT COOPERATION TREATY

PCT

INTERNATIONAL PRELIMINARY EXAMINATION REPORT

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference ASHS/PO8180PC		FOR FURTHER ACTION See Notification of Transmittal of International Preliminary Examination Report (Form PCT/PEA/416)	
International application No. PCT/GB98/00863	International filing date (day/month/year) 20/03/1998	Priority date (day/month/year) 21/03/1997	
International Patent Classification (IPC) or national classification and IPC E21B17/08			
Applicant PETROLINE WELLSYSTEMS LIMITED et al.			
<p>1. This international preliminary examination report has been prepared by this International Preliminary Examining Authority and is transmitted to the applicant according to Article 36.</p> <p>2. This REPORT consists of a total of 7 sheets, including this cover sheet.</p> <p><input checked="" type="checkbox"/> This report is also accompanied by ANNEXES, i.e. sheets of the description, claims and/or drawings which have been amended and are the basis for this report and/or sheets containing rectifications made before this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions under the PCT).</p> <p>These annexes consist of a total of 7 sheets.</p>			
<p>3. This report contains indications relating to the following items:</p> <ul style="list-style-type: none">I <input checked="" type="checkbox"/> Basis of the reportII <input type="checkbox"/> PriorityIII <input type="checkbox"/> Non-establishment of opinion with regard to novelty, inventive step and industrial applicabilityIV <input type="checkbox"/> Lack of unity of inventionV <input checked="" type="checkbox"/> Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statementVI <input type="checkbox"/> Certain documents citedVII <input checked="" type="checkbox"/> Certain defects in the international applicationVIII <input checked="" type="checkbox"/> Certain observations on the international application			
Date of submission of the demand 08/10/1998		Date of completion of this report 19. 07. 99	
Name and mailing address of the International preliminary examining authority:  European Patent Office D-80298 Munich Tel. (+49-89) 2399-0 Tlx 523556 apmu d Fax (+49-89) 2399-4465		Authorized officer Bellingacci, F Telephone No. (+49-89) 2399 2764 	

Form PCT/PEA/409 (cover sheet) (January 1994)

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT**

International application No. PCT/GB98/00863

I. Basis of the report

1. This report has been drawn on the basis of (substitute sheets which have been furnished to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" and are not annexed to the report since they do not contain amendments.):

Description, pages:

2-13	as originally filed		
1	as received on	08/07/1999	with letter of 08/07/1999

Claims, No.:

1-15	as received on	01/06/1999	with letter of 27/05/1999
------	----------------	------------	---------------------------

Drawings, sheets:

1/2	as originally filed		
2/2	as received on	19/06/1999	with letter of 17/06/1999

2. The amendments have resulted in the cancellation of:

- ☐ the description, pages:
☒ the claims, Nos.: 16-20
☐ the drawings, sheets:

3. ☐ This report has been established as if (some of) the amendments had not been made, since they have been considered to go beyond the disclosure as filed (Rule 70.2(c)):

4. Additional observations, if necessary:

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT**

International application No. PCT/GB98/00863

V. Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement**1. Statement**

Novelty (N)	Yes: Claims 1-15
	No: Claims
Inventive step (IS)	Yes: Claims 4, 5, 11-15
	No: Claims 1-3, 6-10
Industrial applicability (IA)	Yes: Claims 1-15
	No: Claims

2. Citations and explanations

see separate sheet

VII. Certain defects in the international application

The following defects in the form or contents of the international application have been noted:

see separate sheet

VIII. Certain observations on the international application

The following observations on the clarity of the claims, description, and drawings or on the question whether the claims are fully supported by the description, are made:

see separate sheet

**INTERNATIONAL PRELIMINARY
EXAMINATION REPORT - SEPARATE SHEET**

International application No. PCT/GB98/00863

Reference is made to the following documents:

D1 = WO,A,96/37680

D2 = WO,A,96/37681

V - Reasoned statement under Rule 66.2 (a)(ii)

V-1 D1, which is considered as the closest prior art, describes an expandable tubing assembly comprising:

- a tubular connector (page 4, lines 14-17 and claim 10) and
- lengths of expandable tubing defining overlapping longitudinal slots with nodes beyond the ends of the slots and having slotted end portions, the tubing being radially expandable by deformation of fingers of material where adjacent circumferentially spaced slots overlap (fig. 3).

The further features of claim 1 are new and therefore the claim meets the novelty requirement of Art. 33(3) PCT.

V-2 D1 does not disclose how the tubular connector should be designed. The solution of a female sleeve joining the male ends of two joints of tubing is however disclosed in D1 as an alternative to a case where a female end of a joint of tubing is connected to male end of the next joint (page 4, lines 14-17). The skilled man will find therefore obvious to design the connection between the female end of the tubular connector and the male end of a joint of tubing in the same way as D1 teaches to design the connection between the female end of a joint of tubing and the male end of the adjacent joint of tubing.

In said connection:

- the female end is slotted;
- male and female parts are connected by connecting means located in the nodes of male and female parts;
- the end most deformable fingers of the female part are axially spaced from the end most deformable fingers of the tubing length (see fig. 3).

The skilled man will find therefore obvious to provide said features also in the

INTERNATIONAL PRELIMINARY

International application No. PCT/GB98/00863

EXAMINATION REPORT - SEPARATE SHEET

connecting tubular, but in doing so he will reach a device as in claim 1. Claim 1 therefore does not meet the inventive step requirement of Art. 33(3) PCT.

It is further pointed out that the subject-matter of claim 1 could even be seen as lacking novelty in the light of D1, as claim 1 does not specify that the tubular connector has two female ends, whereby already a length of slotted tubing could be seen as a "tubular connector", connecting the two adjacent length of tubing as defined in claim 1. In the light of the description the term tubular connector has been interpreted however as comprising two female ends.

V-3 Connecting a female end and a male end of slotted tubing by means of threads machined on the nodes of the two parts is known, see page 3, lines 5-7 and 31-34 of D2.

Given the similarity between the assembly of D1 and D2, the skilled man will find obvious to provide the device of D1 with said feature of D2, and claim 2 therefore does not involve an inventive step.

V-4 As it is apparent that it is advantageous to have a string of tubing with uniform characteristics, no inventive step can be seen in the subject-matter of claim 3.

V-5 None of the cited documents makes suggests to join length of slotted tubing by means of a tubular connector having upset ends. Claim 4, and the dependent claim 5, meet therefore the inventive step requirement of Art. 33(3) PCT.

V-6 The connection between tubing lengths as disclosed in D1 comprises a system of grooves (35) and tongues (36), and therefore the subject-matter of claim 6 does not involve an inventive step.

V-7 The features of claims 7 and 8 are essentially identical to the ones of claims 1, whereby also said claims do not meet the inventive step requirements of Art. 33(3) PCT.

V-8 Claim 9 specifies an obvious ways for designing a connecting sleeve, and therefore the claim does not involve an inventive step.

INTERNATIONAL PRELIMINARY International application No. PCT/GB98/00863
EXAMINATION REPORT - SEPARATE SHEET

V-9 Claim 10 specifies an obvious method for connecting lengths of slotted tubing by means of a connector as in claim 1. As claim 1 does not meet the inventive step requirement of Art. 33(3) PCT, the same applies to claim 10.

V-10 D1, by merely suggesting that two length of slotted tubing can be connected by means of a sleeve, does not make obvious to join the two length by means of strips of material or by means of a sleeve with upset ends. As also the other documents in the proceedings do not make obvious said solution, independent claims 11, 14 and 15, and related dependent claims 12 and 13, meet the requirement of Art. 33(2) PCT.

V-12 Finally, it is pointed out that WO/A, 98/22690 has an effective filing date (i.e. a priority date) earlier than the filing date of the present application but it was published after said date. The document therefore is not part of the prior art as defined in Rule 64.1PCT. It is however possible that the document could be considered as part of the prior art, at least as far a novelty is concerned, by some national or international authority.

VII - Certain defects

VII-1 The independent claims are not properly cast in the two part form, with those features which in combination are part of the prior art (D1) being placed in the preamble, contrary to the requirements of Rule 6.3(b) PCT.

VII-2 The features of the claims are not provided with reference signs placed in parentheses (Rule 6.2(b) PCT).

VII-3 The statement in the description, page 13, last paragraph, does not meet the requirements of Art. 6 PCT as interpreted in the PCT Guidelines, PCT/GL/3 III, 4.3a.

VIII - Certain observations (clarity)

VIII-1 To satisfy the conciseness requirement of Art. 6 PCT the set of claims should include only the minimum necessary number of independent claims in any one

INTERNATIONAL PRELIMINARY

International application No. PCT/GB98/00863

EXAMINATION REPORT - SEPARATE SHEET

category. Said requirement is not satisfied by claims 1, 7, 10, 11, 14, 15, as in the present case it is considered appropriate to use only one independent claim in any category.

EXPANDABLE SLOTTED TUBING STRING AND METHOD FOR
CONNECTING SUCH A TUBING STRING




This invention relates to a connector, and in particular to a connector forming part of an expandable tubing assembly. The invention also relates to a method of connecting lengths of expandable tubing.

5 WO93/25800 describes expandable tubing defining overlapping longitudinal slots. On expansion of the tubing, by pushing or pulling a mandrel through the tubing, the slots expand to form diamond-shaped apertures. The expansion is accommodated by deformation of the fingers of
10 metal between the slots, this deformation taking place predominantly at the slot ends, and also by circumferential extension of the parts of the tubing wall beyond the slot ends. In expandable tubing developed by the applicants radial expansion is achieved with the parts of the tubing
15 wall between and beyond the slot ends experiencing little if any deformation, these parts being known as the tubing "nodes".

Arrangements for connecting lengths of slotted tubing are disclosed in WO96/37681 and WO97/21901, the disclosures
20 of which are incorporated herein by reference. Both of these documents describe arrangements in which the end of one length of tubing defines a male coupling portion which is received within a female coupling portion on the other length of tubing and attached thereto.

25 In another coupling arrangement, the ends of the tubing lengths are received within an external coupling

2/2



CLAIMS

1. An expandable tubing assembly comprising:

5 a tubular connector defining overlapping longitudinal slots and comprising an intermediate portion located between slotted end portions, the connector being radially expandable by deformation of fingers of material in the intermediate portion where adjacent circumferentially spaced slots overlap, and

10 lengths of expandable tubing defining overlapping longitudinal slots with nodes beyond the ends of the slots and having slotted end portions, the tubing being radially expandable by deformation of fingers of material where adjacent circumferentially spaced slots overlap,

15 the connector end portions being coupled to the nodes of respective end portions of the tubing lengths and the deformable fingers of the sleeve being axially spaced from the end most deformable fingers of the respective tubing lengths.

20 2. The assembly of claim 1, wherein the connector end portions and the nodes of the tubing end portions are threaded.

3. The assembly of claim 1 or 2 wherein the intermediate portion is of corresponding configuration of the tubing lengths, such that the expansion characteristics of the

AMENDMENT SHEET

15

connected tubing assembly are substantially constant over the connection.

4. The assembly of claim 3, wherein the connector intermediate portion is of substantially the same wall thickness of the tubing and wherein the connector end portions are upset.

5. The assembly of claim 4 wherein each connector end portion defines an internal thread for engaging a corresponding thread on an outer surface of the respective tubing end portion.

6. The assembly of any of the preceding claims wherein the connector end portions define grooves to receive corresponding tongues provided on the tubing length end portions.

7. An arrangement for coupling lengths of expandable tubing, the arrangement comprising:

a sleeve defining overlapping longitudinal slots and being radially expandable by deformation of fingers of material where adjacent circumferentially spaced slots overlap;

first and second tubing lengths defining overlapping longitudinal slots and being radially expandable by deformation of fingers of material where adjacent circumferentially spaced slots overlap; and

AMENDED SHEET

16

connecting means for connecting the sleeve to the ends of the tubing lengths, ends of the tubing lengths being received by respective ends of the sleeve,

5 the deformable fingers of the sleeve being axially spaced from the end most deformable fingers of the respective tubing lengths.

8. The arrangement of claim 7, wherein the connecting means are provided at circumferentially spaced locations at the end of the tubing lengths beyond the end most tubing fingers, and at the ends of the sleeves beyond the
10 respective end most tubing fingers.

9. The arrangement of claim 7 or 8, wherein the sleeve and the tubing lengths are each of substantially constant diameter along their length.

15 10. A method of coupling the ends of first and second lengths of expandable tubing and expanding the coupled tubing lengths, the method comprising the steps of:

providing a sleeve defining overlapping longitudinal slots and deformable fingers of material where adjacent
20 circumferentially spaced slots overlap;

providing first and second lengths of expandable tubing defining overlapping longitudinal slots and deformable fingers of material where adjacent circumferentially spaced slots overlap;

25 coupling the sleeve to the ends of first and second

AMENDED DRAFT

17

lengths of expandable tubing such that the fingers of the sleeve are longitudinally spaced from the end most fingers of the tubing lengths; and

5 forcing an expansion member through the connected tubing lengths to expand the sleeve and the tubing lengths.

11. An arrangement for coupling lengths of expandable tubing, the arrangement comprising: a sleeve of longitudinally extending strips of metal; first and second tubing lengths defining overlapping longitudinal slots and
10 being radially expandable by deformation of fingers of material where adjacent circumferentially spaced slots overlap; and connecting means for connecting the sleeve to the ends of the tubing lengths.

12. The arrangement of claim 11, wherein the strips are
15 rectilinear.

13. The arrangement of claim 11 or 12, wherein the strips are initially circumferentially connected by frangible links.

14. A method for coupling the ends of first and second
20 lengths of expandable tubing defining overlapping longitudinal slots and deformable fingers of material where adjacent circumferentially spaced slots overlap, the method comprising the steps of:

providing a sleeve comprising longitudinally extending

18

strips of material;

coupling the sleeve to the ends of first and second
lengths of expandable tubing; and

5 forcing an expansion member through the connected
tubing lengths to expand the sleeve and tubing lengths.

15. An expandable tubing assembly comprising:

10 a tubular connector defining overlapping longitudinal
slots and comprising an intermediate portion between
slotted upset end portions; and

lengths of expandable tubing defining overlapping
longitudinal slots and having slotted end portions defining
nodes beyond the ends of the slots, the connector end
portions being coupled to the nodes of respective end
15 portions of the tubing lengths,

the connector intermediate portion being of
substantially the same wall thickness as the tubing, such
that the expansion characteristics of the connected tubing
assembly are substantially constant over the connection.

